

# Leica CS20 Data sheet



Dominant performance through seamless integration

The next generation of Leica Nova and Viva measuring instruments become the world's first self-learning total stations and MultiStation with Leica Captivate. Transforming the Leica Viva GNSS experience, this engaging software joins ultimate GNSS receiver innovation with an industry-first 3D user immersion. Leica Captivate modernises the Leica Nova scanning experience, for the first time merging the overlay of measured points, 3D models and point clouds into a single view.



Infinitely bridging the field to the office

While Leica Captivate captures and models data in the field, Leica Infinity processes the information back in the office. A smooth data transfer ensures the project stays on track. Leica Captivate and Leica Infinity work in conjunction to join previous survey data and edit projects faster and more efficiently.

**ACC»**

Customer care only a click away

Through Active Customer Care (ACC), a global network of experienced professionals is only a click away to expertly guide you through any problem. Eliminate delays with superior technical service, finish jobs faster with excellent consultancy support, and avoid costly site revisits with online service to send and receive data directly from the field. Control your costs with a tailored Customer Care Package, giving you peace of mind you're covered anywhere, anytime.



# Leica CS20



Leica CS20 Basic



Leica CS20 LTE

Leica CS20 LTE Disto

## SYSTEM SPECIFICATIONS

Operating system	Windows EC7		
Processor	TI OMAP4430 1GHz Dual-core ARM@ Cortex™-A9 MPCore™		
Memory (RAM)	2 GB		
Internal storage (Max)	4 GB		
Screen size (Diagonal) & orientation (Primary)	5" (127mm), Landscape, sunlight-readable		
Screen resolution & type	800 x 480 WVGA, Colour TFT		
Weight (including battery)	1115 g	1190 g	1225 g
Size (length x width x depth)	284mm x 150mm x 49mm		
Batteries	11.1V, 2.8Ah Li-Ion		
Battery life	8 hours		

## ENVIRONMENTAL SPECIFICATIONS

Dust / Water resistance	IP68		
Shock resistance	1.2m (4 ft) / MIL-STD-810F, Method 514.5 – Cat24		
Operation temperature	-30°C to +60°C		
Storage temperature	-40°C to +80°C		
Military standard (MIL.-STD)	810F		

## CONNECTIVITY

SD/SDHC	✓
USB client	✓
USB host	✓
Serial RS232	✓
Power jack	✓
Integrated Bluetooth®	✓
Integrated WLAN	✓

## USER INTERFACE

Touch screen	✓
On screen keyboard	✓
Keypad type	QWERTY keypad
Number of keys	67

## INTEGRATED PERIPHERALS

DISTO™			✓
UMTS/LTE Cellular modem		✓	✓
5 MP Camera	✓	✓	✓
Flash	✓	✓	✓
Compass	✓	✓	✓
Accelerometer	✓	✓	✓
Gyro	✓	✓	✓
Long-range Bluetooth®		✓	✓
Expansion pack		✓	✓

- when it has to be **right**



The Bluetooth® trademarks are owned by Bluetooth SIG, Inc.  
Laser radiation, do not stare into beam. Class 2 laser product according to IEC 60825-1:2014.

Illustrations, descriptions and technical data are not binding. All rights reserved.  
Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2019.  
913453en - 11.19

Leica Geosystems AG  
Heerbrugg, Switzerland  
www.leica-geosystems.com



A TRADITION IN PRECISION

Seattle 425-771-7776 | Tacoma 253-922-6087  
Portland 503-641-3388 | Salt Lake City 801-878-9763  
St. George 702-586-1152 | Las Vegas 702-586-1152  
Boise 208-369-4388

**www.KukerRanken.com**