

Leica iCON CC200 Field controller Datasheet



LEICA iCON CC200 – Your new on-site partner!

- Large 10" screen size
- Increased performance, ideal for handling large amounts of data
- Hard keys with user-customisable shortcuts
- 'Glove' and 'rain' modes for all weather conditions
- Up to 12 hours operating time
- Anti-reflective (AR) screen
- 'Portrait' mode to support specific applications

The rugged 10" Leica iCON CC200 field controller is your on-site partner that promises to deliver longer operating times and more comfort, thanks to its single 12-hour battery and large screen. The iCON CC200 is designed to smoothly handle use cases requiring large amounts of data. Used in combination with Leica iCON site or Leica iCON build construction field software, it is the ideal solution for all positioning and measuring tasks on your construction site – including on-machine applications.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica iCON CC200 Field controller



MODEL

CC200

Operating system	Microsoft Windows® 10 enterprise LTSC
CPU platform	Intel® Core™ i5-10310U vPro™ processor 1.7 GHz with Turbo Boost up to 4.4 GHz, 6 MB cache
RAM	16 GB
Data storage	512 GB OPAL SSD
Display	10" widescreen, 1920 × 1200 resolution, anti-reflective (AR) screen, Intel UHD Graphics, concealed mode; day/night mode, Gorilla Glass 3, 10-finger multitouch
Display branding	Printed display glass
Keyboard & buttons	IP55 2-button digitiser pen (right click & erase), stylus holder, tether and cleaning cloth Supports 'glove' and 'rain' mode 7 tablet buttons (3 user-definable, A1/A2/A3) On-screen QWERTY keyboard
I/O ports	1 x USB-C v5.1; 1 x USB A v5.1; Docking station connector (24 pin); Integrated dual-array microphone; Integrated 88 db speakers; Intel high definition audio compliant

COMMUNICATIONS

Integrated communications	Integrated 4G LTE multi-carrier mobile broadband; Intel Wi-Fi 6 AX201; Bluetooth® v5.1 (Class 1) ¹
Integrated GPS	L1 GNSS integrated (depending on country variant)
Integrated camera	1080p webcam with privacy cover & dual-array microphone – infrared with Windows Hello support 8 MP rear camera with autofocus and LED flash
TPS 1-man mode working range ²	Typically 450 m, up to 500 m with direct line of sight

POWER MANAGEMENT

Battery	Li- ion long 'life' battery: 10.8 V, 6300 mAh
Operating Time ³	12 hours (max. load test)

SPECIFICATIONS

Size	27.94 cm x 18.8 cm x 2.8 cm (11.0" x 7.4" x 1.1")
Weight	1.3 kg (2.9 lbs)
Operating temperature	-30 °C (-20 °F) to 60 °C (140 °F)
Storage temperature	-50 °C (-60 °F) to 70 °C (160 °F)
Rain and dust	IP65
Humidity	95% RH temp cycle 32 °C (91 °F) / 71 °C (160 °F)
Drop	1.80 m
Vibration	General minimum integrity and helicopter minimum integrity test, MIL-STD-810H, Method 514.8, Procedure I, II

1) Availability of 4G LTE modem dependent on country variant.

2) Range varies depending on local conditions.

3) In continuous field operation mode. May vary with temperature, battery age etc.

Leica iCON. Understanding construction.



A TRADITION IN PRECISION

Seattle 425-771-7776

Tacoma 253-922-6087 | Portland 503-641-3388

Salt Lake City 801-878-9763 | Boise 208-369-4388

www.KukerRanken.com

- when it has to be **right**

Leica
Geosystems