

# Leica iCON CC180

## Field controller

### Datasheet



#### LEICA iCON CC180 – Where compactness meets performance!

- 8" LCD display with exceptional visibility
- Intel® 12th Generation high-performance processors
- Fan-less design for reduced device noise
- Finger/rain, glove, or stylus operation modes
- High-duty battery with up to 8 hours of operation
- 500 m Bluetooth® connectivity range

The Leica iCON CC180 is a compact, reliable field controller tailored to the requirements of construction professionals. This high-performing device utilises the power of the Intel® 12th Gen processor to enable swift processing of complex construction designs. Beyond its traditional use cases, it extends its capability by supporting the iCON site machine indicative guidance for cut and fill earthmoving jobs and the iCON site excavator application. The Leica iCON CC180 carries assured quality and is a handy tool for building and heavy construction industry professionals.

[leica-geosystems.com](https://www.leica-geosystems.com)



- when it has to be **right**

**Leica**  
Geosystems

# Leica iCON CC180 Field controller



<b>MODEL</b>		<b>iCON CC180</b>
Operating system	Microsoft Windows® 10 IoT Enterprise LTSC	
CPU platform	Intel® Pentium® Gold 8500 Processor (up to 4.4GHz)	
RAM	8 GB	
Data storage	128 GB	
Display	8" LCD screen; resolution 1280 x 800, 800 nits DynaVue® sunlight readable display with capacitive multi-touch screen, user-selectable touch mode for finger/water, glove or stylus	
Keyboard & buttons	3 buttons (1 user-definable key), on-screen QWERTY keyboard	
I/O ports	Thunderbolt 4 x 1, USB 3.2 Gen2 (type C) x 1 (supports DP), Audio in/out (combo jack) x 1, microSD card (microSDXC) x 1, Docking connector (20-pin Pogo) x 1, Nano SIM card x 1, DC-In jack x 1	
<b>COMMUNICATIONS</b>		
Integrated communications	Multicarrier 4G LTE Mobile Broadband + GPS Combo, WLAN WiFi6E; Bluetooth® v5.3 <sup>1</sup>	
Integrated camera	Integrated 2.0 MP front-facing camera Integrated 8.0 MP auto-focus rear camera with flash	
TPS 1-man mode working range <sup>1</sup>	Typically 450 m, up to 500 m with direct line of sight	
<b>POWER MANAGEMENT</b>		
Battery	Li-Ion 7.6V, 7200mAh	
Operating Time <sup>2</sup>	Up to 8 hours (max. load test)	
<b>SPECIFICATIONS</b>		
Size	227 x 150 x 30.5 mm (8.94" x 5.90" x 1.2") (incl. battery)	
Weight	974 g (2.14 lbs) (incl. battery)	
Operating temperature	-20 °C to 60 °C (-4 °F to 140 °F)	
Storage temperature	-46 °C to 71 °C (-51 °F to 160 °F)	
Rain	IP66	
Dust	IP66	
Drop	1.80 m (6 ft)	
Vibration	MIL-STD 810H (drop, shock, vibration, rain, dust, altitude, freeze/thaw, high/low temperature, temperature shock, humidity) MIL-STD 461G (conduction, radiation, conducted susceptibility, radiated susceptibility)	
<b>REGULATORY</b>		
Compliance	CE/RED, SAR, UKCA, FCC, PTCRB, Verizon, IC, TELEC & JATE, PSE, RMC	
<b>SUSTAINABILITY</b>		
Compliance	WEEE, RoHS, J-MOSS	

1) Range varies depending on local conditions.

2) In continuous field operation mode. May vary with temperature, battery age, etc.

Leica iCON. Understanding construction.



A TRADITION IN PRECISION

Seattle 425-771-7776

Tacoma 253-922-6087 | Portland 503-641-3388

Salt Lake City 801-878-9763 | Boise 208-369-4388

[www.KukerRanken.com](http://www.KukerRanken.com)

- when it has to be **right**

